

## Technical Specifications Voice Server Espero

### General

Part no. 4 ch	030.02210
Part no. 8 ch	030.02212
Part no.16 cha	030.02410
Part no. 30 cha	030.02412
Working temperature	0 - 40°C
Size	26 x 19x 5,5 [desktop] 44 x 31,5 x 9,5 cm [19" rack]
Weight	1200 grams [desktop] 6000 grams [19" rack]
Colour	Ruby, RAL 3004
CryptoCard	Credit Card size external, Mini Size Internal [desktop] Credit Card Size Internal, Mini Size Internal [19" rack]
Power	input 90-264V~ 47-63Hz, output 10V= @2A [desktop] input 90-264V~ 47-63Hz, output 5V= @4A, output 12V= @3.75A [19" rack]
Connections	<b>Type</b>
Telecom connectivity	2x ISDN Basic rate = 2 channels/line and Sniffer 'in line' on RJ45intended for use with <b>special</b> RJ45 T-splitter 4x ISDN Basic rate = 2 channels/line and Sniffer 'in line' on RJ45intended for use with <b>special</b> RJ45 T-splitter ISDN Primary Rate (upto 30 ch / line) on 2x RJ45, NT and TE
Audio connectivity	Headset on 2 pcs 3,5mm mini jack (red=mic, black=spk)
Miscellaneous	internal speaker

Approvals	Type
EMC	EN55022 ClassB
	EN55024ClassB
	FCC15 subpartB
Safety	EN60950
Telecom	TBR3
	TBR4