

Single Flash 5

General	
Part no.	010.01625 (5 hours)
Part no. Rec. double capacity upgrade	010.01622 (10 hours)
Part no.	010.02081 CD recorder + Quick CD access software
Working temperature	0 - 40°C
Size without handset	26 x 19 x 5,5 cm
size with handset	26 x 23 x 8,5
Weight	900 grams 1100 grams with optional CD recorder
CryptoCard	Credit Card size external
Power	input 230V~ 50Hz, output 7,5V~ @2A [Europe] input 120V~ 60Hz, output 7,15V~ @2A [USA] input 230V~50Hz, output 6,8V~ @2A [UK] input 90-264 V ~ 47...63Hz, output 10V= @2A [with CD recorder]

Connections	Type
Telecom connectivity	POTS 2x RJ12 one for input and one for output Handset on 2xRJ10, one for handset in and one for handset out
Audio connectivity	Headset on 2pcs 3,5mm jack (red=mic, black=spk)
Miscellaneous	internal speaker

Approvals	Type
EMC	EN55022 ClassB EN55024ClassB FCC15 subpartB
Safety	EN60950
Telecom	TBR21

Single HD9900

General	
Part no.	010.01600 (20.700 hours)
Part no.	010.02081 CD recorder + Quick CD access software
Part no. Rec. Double capacity upgrade	010.02082 (41.400 hours)
Working temperature	0 - 40°C
Size without handset	26 x 19 x 5,5 cm
size with handset	26 x 23 x 8,5
Weight	1000 grams 1200 grams (with optional CD recorder)
CryptoCard	Credit Card size external
Power	input 230V~ 50Hz, output 7,5V~ @2A [Europe] input 120V~ 60Hz, output 7,15V~ @2A [USA] input 230V~50Hz, output 6,8V~ @2A [UK] input 90-264 V ~ 47...63Hz, output 10V= @2A [with CD recorder]
Connections	Type
Telecom connectivity	POTS 2xRJ12 one for input and one for output Handset on 2xRJ10 , one for handset in and one for handset out
Audio connectivity	Headset on 2pcs 3,5mm jack (red=mic, black=spk)
Miscellaneous	internal speaker
Approvals	Type
EMC	EN55022 ClassB EN55024ClassB FCC15 subpartB
Safety	EN60950
Telecom	TBR21

Single Digital SD2750

General	
Part number	010.01630
Working temperature	0 - 40°C
Size without handset	26 x 19 x 5,5 cm
Weight	1000 gram
CryptoCard	Credit Card size external
Power	input 90-264V~ 47-63Hz, output 10V~ @2A
Connections	Type
Telecom connectivity	ISDN2IO = ISDN basic rate (2 channels / line) one incoming RJ45 jack and one outgoing RJ45 jack UP0 = 2 wire digital PBX support for Siemens, Philips and Avaya brands, one incoming RJ45 jack and one outgoing RJ45 jack
Audio connectivity	Headset on 2pcs 3,5mm jack (red=mic, black=spk)
Miscellaneous	internal speaker
Approvals	Type
EMC	EN55022 ClassB EN55024ClassB FCC15 subpartB
Safety	EN60950
Telecom	TBR21